


HC-49U 技术指标:

指 标 名 称 PARAMETER		值和单位 Value and Unit		条 件 conditions	
频 率 Nominal Frequency		1MHz - 160MHz		25℃	
静态电容 Shunt Capacitance (C0)		≤7pF			
驱动电平 Drive Level		1~500μW (100μW Typ.)			
负载电容 Load Capacitance		8PF/12PF/16PF/20pF or specify			
频率稳定度 Frequency stability	温度稳定度 VS Temperature	≤±5ppm/±10ppm/±25ppm or specify		-20℃~+70℃	
		≤±10ppm/±30ppm/±50ppm or specify		-40℃~+85℃	
	年老化率 Aging	≤±3ppm		First year	
	频率准确度 Calibration frequency	≤±5ppm/±10ppm/±25ppm or specify		25℃	
温度范围 Temperature Range	工作温度 Operating temperature	-20℃~+70℃ or specify			
	储藏温度 Storage temperature	-55~125℃			
等效串联电阻 Equivalent Series Resistance (R0)					
基频 Fundamental		三次泛音 3 rd Overtone		五次泛音 5 th Overtone	
1~3.0MHz	≤350 Ω	20~25MHz	≤50 Ω	70~100MHz	≤60 Ω
3~3.5MHz	≤150 Ω	25~30MHz	≤40 Ω	100~125MHz	≤60 Ω
3.5~4.0MHz	≤90 Ω	30~75MHz	≤40 Ω	125~160MHz	≤60 Ω
4~7.0MHz	≤60 Ω	75~100MHz	≤60 Ω		
7~15MHz	≤35 Ω				
15~30MHz	≤25 Ω				

PACKAGE:

UNITS:MM





武汉恒达高科电子有限公司

Wuhan Hengda Gaoke Electronics CO.,LTD.

晶体谐振器系列



晶体谐振器

公司名称	产品型号	震动模式	常温频差	温度频差	温度范围	负载电容	频率
HDE-	49U: Hc-49U 49S: HC-49S 49M: HC-49SMD M75: SMD7050 M53: SMD5032 M32: SMD3225 M22: SMD2520 M21: SMD2016 M11: SMD1612	F:基频 T: 三次泛音 R: 五次泛音	C: $\pm 100\text{ppm}$ D: $\pm 50\text{ppm}$ E: $\pm 30\text{ppm}$ F: $\pm 20\text{ppm}$ G: $\pm 10\text{ppm}$ H: $\pm 5\text{ppm}$	C: $\pm 100\text{ppm}$ D: $\pm 50\text{ppm}$ E: $\pm 30\text{ppm}$ F: $\pm 20\text{ppm}$ G: $\pm 10\text{ppm}$ H: $\pm 5\text{ppm}$	B:0 ~+50℃ C: 0 ~+70℃ D:-10~+60℃ E:-20~+70℃ F:-30~+80℃ G:-40~+85℃	** - 表示 负 责 电 容	***: 表示频率
例如: HDE-49SFFFG30-25.000							
HDE	49S	F	F	F	G	30	25.000
公司简称	HC-49S	基频	常温频差 $\pm 20\text{ppm}$	温度频差 $\pm 20\text{ppm}$	-40~+85℃	负载电容 30pF	标称频率: 25.000MHz
说明: 武汉恒达高科电子有限公司生产 49S 晶体 频率 25MHZ 基频率; 常温频差 $\pm 20\text{ppm}$; 温度频差 $\pm 20\text{ppm}$; 工作温度-40~+85℃; 负载电容: 30pF							