


HC-49S 技术指标:

指标名称 PARAMETER		值和单位 Value and Unit	条 件 conditions
频 率 Nominal Frequency		3MHz - 100MHz	25℃
静态电容 Shunt Capacitance (C0)		≤7pF	
驱动电平 Drive Level		1~500μW (100μW Typ.)	
负载电容 Load Capacitance		8PF/12PF/16PF/20pF or specify	
频率稳定度 Frequency stability	≤±5ppm/±10ppm/±25ppm or specify	≤±10ppm/±20ppm/±30ppm or specify	-20℃~+70℃
		≤±20ppm/±30ppm/±50ppm or specify	-40℃~+85℃
	年老化率 Aging	≤±3ppm	First year
	频率准确度 Calibration frequency	≤±5ppm/±10ppm/±25ppm or specify	25℃
温度范围 Temperature Range	工作温度 Operating temperature	-20℃~+70℃ or specify	
	储藏温度 Storage temperature	-55~125℃	
等效串联电阻 Equivalent Series Resistance (R0)			
基频 Fundamental		三次泛音 3 rd Overtone	五次泛音 5 th Overtone
3~3.79MHz	≤200 Ω	27~30MHz	≤100 Ω
3.8~5.0MHz	≤150 Ω	30~50MHz	≤80 Ω
5~10MHz	≤80 Ω	50~100MHz	≤60 Ω
10~14MHz	≤40 Ω		
14~36MHz	≤30 Ω		

PACKAGE:

UNITS:MM





晶体谐振器

公司名称	产品型号	震动模式	常温频差	温度频差	温度范围	负载电容	频率
HDE-	49U: Hc-49U 49S: HC-49S 49M: HC-49SMD M75: SMD7050 M53: SMD5032 M32: SMD3225 M22: SMD2520 M21: SMD2016 M11: SMD1612	F:基频 T: 三次泛音 R: 五次泛音	C: $\pm 100\text{ppm}$ D: $\pm 50\text{ppm}$ E: $\pm 30\text{ppm}$ F: $\pm 20\text{ppm}$ G: $\pm 10\text{ppm}$ H: $\pm 5\text{ppm}$	C: $\pm 100\text{ppm}$ D: $\pm 50\text{ppm}$ E: $\pm 30\text{ppm}$ F: $\pm 20\text{ppm}$ G: $\pm 10\text{ppm}$ H: $\pm 5\text{ppm}$	B:0 ~+50℃ C: 0 ~+70℃ D:-10~+60℃ E:-20~+70℃ F:-30~+80℃ G:-40~+85℃	** - 表示 负 责 电 容	**.***: 表示频率
例如: HDE-49SFFFG30-25.000							
HDE	49S	F	F	F	G	30	25.000
公司简称	HC-49S	基频	常温频差 $\pm 20\text{ppm}$	温度频差 $\pm 20\text{ppm}$	-40~+85℃	负载电容 30pF	标称频率: 25.000MHz
说明: 武汉恒达高科电子有限公司生产 49S 晶体 频率 25MHZ 基频率; 常温频差 $\pm 20\text{ppm}$; 温度频差 $\pm 20\text{ppm}$; 工作温度-40~+85℃; 负载电容: 30pF							